



Extreme weather and impact protection

Against hailstorm, rain, snow, heat and wind Our products have achieved Class 4 ratings according to the UL 2218 Roof Impact Classifications



Fire protection

We got an "A" in fire protection according to the UL 790 (ASTM E 108) Fire Protection Ratings



High wind protection

We achieved the Class 90 certification for the UL 580 Wind Uplift Resistance test. We have tested our products at wind speeds over 200 mph








The quality of our roofs has been recognized and certified by the Underwriters Laboratories.


UL is the largest independent testing laboratory in the world. It is dedicated to promoting safe living and working environments.
















Weight of one pallet:

2920 lb

Quantity per pallet:

350 pcs

Effective surface area of one pallet:

3032 sq. ft

Weight of one pallet:

2650 lb

Quantity per pallet:

319 pcs

Effective surface area of one pallet:

2739 sq. ft



Simple transport

One pallet contains over 3000 sq. ft (Supre), 2700 sq. ft (Ulta) of material – enough to cover an average size roof



Easy to install

Pre-drilled holes and modular assembly speed up installation and reduce mistakes



Cost effective installation

Our products average less than 5% waste during installation compared to industry norms greater than 10%

Take to the sky with Raven Black

Ravens are very intelligent birds, which played an integral role in the mythology of the indigenous peoples of the Pacific Northwest, as well as art and literature.

For many cultures the bird was a religious symbol. Some even believed that it was God. Raven Black. The color of freedom

Dive deep into the Pacific Gray

The Pacific is the largest and deepest ocean on Earth. It covers almost 1/3 of the earth's surface. Its depth reaches more than 35 thousand feet.

Pacific Gray. The color of mystic nature

Raven Black WE TAKE PRIDE IN EVERY COLOR Sierra Brown Pacific Gray Canyon Red

Dare to conquer with Sierra Brown

The Sierra Nevada is a mountain range in the Western United States.


Its highest peak — Mount Whitney — reaches an elevation of 14.505 feet.

The foothills of this mountain range are home to the California Gold Rush of the 19th century.


Sierra Brown. The color of a true conqueror

Experience Canyon Red – one of nature's true wonders

The Grand Canyon is the largest river gorge in the world, located in Arizona. It is 277 miles long, about 6.000 feet deep and the home of whitewater rafting. Canyon Red. The color of adventure








Supre





3.77 ft	3.9 ft	8.16 lb

8.66 sq. ft 350 pcs 3032 sq. ft 0.805 sq. m 281.75 sq. m



Ulta





SYSTEM

53/4"/31/2"

COLORS



Brown ~RAL 8028/8017 GreenCoat RWS 434



Graphite ~RAL 7011 GreenCoat RWS 087



Black ~RAL 9005 GreenCoat RWS 015



White ~RAL 9002 GreenCoat RWS 001



Brick-red ~RAL 8004 GreenCoat RWS 742

30 YEAR

WARRANTY

GREENCOAT® RWS

SSAB

The colors shown are illustrative and may vary from the actual ones.

RAIN-THIRSTY FLAMINGO



GUTTER SYSTEM ELEMENTS

- 1. Gutter
- 2. Joint connector
- 3. Fascia hanger
- 4. Inside corner
- 5. Outside corner
- 6. End cap
- 7. Drop outlet
- 8. Elbow
- 9. Downspout
- 10. Downspout heavy duty mount
- 11. Downspout strap anchor
- 12. Downspout wall bracket
- 13. Downspout connector
- 14. Outflow elbow
- 15. Rain catcher
- 16. Tee connector
- 17. Rain trap



Patent pending Rp14731, Rp17669, Rp18757 RWU66816, RWU68626



Excellent tightness

Flamingo elements are moulded in specially designed, patented moulds. Forget about the leaks when assembled



Only the best materials

Flamingo was manufactured from GreenCoat RWS
(Rain Water System) steel produced by SSAB – a Swedish
global steel company. GreenCoat RWS was developed
specifically to create high quality gutter systems

It has a double sided coating and is exceptionally durable.

Coatings used in GreenCoat RWS products include polymer grains, which improve the surface scratch resistance



Evenness for years

Flamingo has a 30-year warranty for the C1-C4 environmental class (industrial and coastal areas with a high aggressiveness of the corrosive environment)



Safe transport and storage

Flamingo elements are factory-protected with foil.

We transport it in specially designed packaging and care about the highest standard of storage







OUTSIDE CORNER



JOINT CONNECTOR



INSIDE CORNER
90°



FASCIA HANGER



END CAP



DOWNSPOUT



DOWNSPOUT CONNECTOR







TEE CONNECTOR RAIN CATCHER

OUTFLOW ELBOW







High resistance to environmental conditions

GreenCoat RWS products are a lightweight construction material with a beautiful shine. They are very resistant to corrosion, UV rays and scratches



Complete steel roof

Flamingo is ideally suited with Worthouse Modular Roofing Tiles



Easy and fast assembly

Flamingo components are made with care for the smallest detail and fit together perfectly, making the assembly fast and easy



Extra strong gutter hangers

Flamingo hanger can easily carry weight of 165 lbs



The system is made of the best quality steel covered with zinc 0.90 oz/ft²



Proven system

It is the best system for metal roofing. Recommended by roofers. Flamingo has been a success for many years



Gold Medal MTP BUDMA 2010 for the Flamingo Steel Gutter System

DIMENSIONS

Covering width 12"

306 mm

Panel height


1/2"

12.2 mm

Panel length

10'

3000 mm



COLORS

Traditional



Black ~RAL 9005







The colors shown are illustrative and may vary from the actual ones.

Wood grain



Golden Oak Wood grain



Dark Oak Wood grain




Winchester Oak Wood grain

PVC SOFFIT

STANDARD PANEL

VENTED PANEL

















J-channel

Traditional — Wood grain



H-channel

Traditional — Wood grain



Inside corner

Traditional — Wood grain





Outside corner


Traditional — Wood grain


4CCESSORIES


#smartmetalroofing





















































RIDGE VENT ROLL

12 in x 16.5 ft (310 mm x 5 mb)





Extreme weather protection against hailstorm, rain, snow, heat and wind



One pallet – one job



Lightweight and easy to handle



Pre-drilled holes enable self-calibration of roof



Easy and space efficient storage



Quick and efficient installation



Roof angle and partially installed roof corrections



Batch-to-batch color consistency guarantee



Less than 5% material waste



Complete set of accesories



High wind resistance



Fire protection – class A degree

Worthouse.® Inc.

2315 Landmeier Rd

Elk Grove Village

IL 60007

Tel: 847 621 2470

Tel: 847 621 2951

worthouse @worthouse.com

worthouse.com